

FF TLF 1500

Small rescue pumper

Made in Croatia



Characteristics

- ❖ The Flammifer FF TLF 1500 is a small rescue vehicle, 7t GVW, with a crew cabin for up to 7 persons.
- ❖ It is intended for fire extinguishing in towns and cities with highly inaccessible narrow streets where its width of 2,10 m comes to the fore.
- ❖ The fire engine is equipped with a fire extinguishing pump of normal pressure, one rapid intervention hose reel, a normal pressure water /foam nozzle and a 1500 litres water tank located in the central part of the fire engine's superstructure.



FLAMMIFER



Flammifer d.o.o • Ulica akademika Milana Heraka 22 • 47280 Ozalj • Croatia

Tel.: +385 (0)47/731-048 • +385 (0)47/731-068 • +385 (0)47/ 731-088 • Fax: +385 (0)47/731-008 • GSM: +385 (0)91/6645-631

www.flammifer.hr • www.facebook.com/FlammiferOzalj • flammifer@flammifer.hr



Basic firefighting equipment

- ❖ 1500 L water tank made of PE-HD
- ❖ Normal pressure pump: FPN 10-10000
- ❖ Rapid intervention hose reel of 25 m in length with electrical reeling and water nozzle
- ❖ Ladders for roof access to superstructure
- ❖ Brackets of firefighting equipment defined by client

Superstructure

- ❖ Complete superstructure is made of light material (aluminium)
- ❖ Three aluminium roller shutters with a bar lock on each side of the vehicle
- ❖ On the back side door or roller shutter with a bar lock
- ❖ Internal superstructure LED Lighting is turned on during opening of the superstructure
- ❖ LED lighting of the surroundings, laterally and back
- ❖ Easy removal of firefighting equipment and its large transparency
- ❖ Heavier equipment fitted low and easily accessible



Chassis

Main characteristics of the chassis:

- ❖ Iveco Daily 70C18 DC 4x2 EURO 6
- ❖ Crew cab for 7 persons (1+2+4)
- ❖ Wheelbase: 3750mm
- ❖ Engine power: 180HP/132 kW
- ❖ Dimensions of the vehicle: LxWxH: 6170x2100x2650 mm
- ❖ GVW: 7.000 kg

Option

- ❖ High pressure module with the pump capacity 42l/100 bar powered by petrol engine, 14 HP/10,2 kW, with electrical and manual ignition.
- ❖ Equipped with high pressure hose reel with hose 13 mm in diameter and 60 m in length, with electrical reeling, foam mixing device 1-6% within the pump and automatic accelerator
- ❖ Light mast with 2 or 4 LED reflectors and pneumatic extraction
- ❖ Rescue winch

Signalization

- ❖ Signalization of the vehicles according to regulations for firefighting vehicles
- ❖ LED Signal light bar on roof of the vehicle
- ❖ Two LED flashlights on the front and the back of the vehicle
- ❖ Multi-tonal fire siren with PA system
- ❖ Setup for installation of radio
- ❖ All the main signs on the client's language
- ❖ All other signalization according to national regulations



POSSIBILITY OF INSTALLATION OF THE BRACKET AND ARRANGEMENT OF FIREFIGHTING EQUIPMENT ACCORDING TO CLIENT'S REQUIREMENTS.