

FF TLF 3000 WF

Wildland fire engine

Made in Croatia



Characteristics

- ❖ The Flammifer FF TLF 3000 WF is a Wildland fire engine, 10,3 t GVW, with a short cab for up to 3 persons.
- ❖ It is intended for forest fire extinguishing and also extinguishing fires in open spaces. The four wheel drive is adaptable to all types of terrains and difficult tasks.
- ❖ The adjustable chassis provides great rigidity and exceptional flexibility on a demanding terrain. The outer part of superstructure is made with mechanical protection.
- ❖ The fire engine contains basic equipment for extinguishing forest fire and undergrowth fire. It is equipped with a fire extinguishing pump of normal and high pressure, one high pressure rapid intervention hose reel with high pressure water/foam nozzle and a 3000 litres water tank located in the central part of the fire engine's superstructure.



FLAMMIFER



Flammifer d.o.o • Ulica akademika Milana Heraka 22 • 47280 Ozalj • Croatia

Tel.: +385 (0)47/731-048 • +385 (0)47/731-068 • +385 (0)47/ 731-088 • Fax: +385 (0)47/731-008 • GSM: +385 (0)91/6645-631

www.flammifer.hr • www.facebook.com/FlammiferOzalj • flammifer@flammifer.hr



Basic firefighting equipment

- ❖ 3.000 L water tank made of PE-HD
- ❖ Normal and high pressure pump type:
 - FPN 10-2500, FPH-40-250
- ❖ High pressure rapid intervention hose reel of 60 or 80 m in length with electrical reeling and high pressure water/foam nozzle
- ❖ Ladders for roof access to superstructure
- ❖ Brackets of firefighting equipment defined by client
- ❖ Rescue winch with capacity of 5000kg

Superstructure

- ❖ Complete superstructure is made of light material (aluminium)
- ❖ External mechanical protection made out of aluminium tubes
- ❖ Two aluminium roller shutters with bar lock on each side of the vehicle
- ❖ On the back side door or roller shutter with a bar lock
- ❖ Internal superstructure LED Lighting that is turned on during opening of the superstructure
- ❖ LED lighting of the surroundings, laterally and back
- ❖ Easy removal of firefighting equipment and its large transparency
- ❖ Heavier equipment fitted low and easily accessible



Signalization

- ❖ Signalization of the vehicles according to regulations for firefighting vehicles
- ❖ LED Signal light bar on the roof of the vehicle
- ❖ Two LED flashlights on the front and the back of the vehicle
- ❖ Multi-tonal fire siren with PA system
- ❖ Setup for installation of radio
- ❖ All the main signs on the client's language
- ❖ All other signalization according to national regulations



Chassis

Main characteristics of the chassis:

- ❖ Mercedes Unimog U4023 4x4 EURO 6
- ❖ Short cab for 3 persons (1+2)
- ❖ Wheelbase: 3850 mm
- ❖ Engine power: 231 HP/170 kW
- ❖ Dimensions of the vehicle:
 - LxWxH: 6515x2330x2835 mm
- ❖ GVW: 10.300 kg

Option

- ❖ Light mast with 4 LED reflectors and pneumatic extraction
- ❖ Roof turret: capacity of 1,600 lit./min, foldable with manual control of engine's RPM
- ❖ Second HP rapid intervention hose reel with 60 or 80 m of hose
- ❖ NP rapid intervention hose reel with 25 m of hose

POSSIBILITY OF INSTALLATION OF THE BRACKET AND ARRANGEMENT OF FIREFIGHTING EQUIPMENT ACCORDING TO CLIENT'S REQUIREMENTS.