

FF TLF 5000

Tank pumper

Made in Croatia



Characteristics

- ❖ The Flammifer FF TLF 5000 is a tank pumper, 16t GVW, with a short cab for up to 3 persons .
- ❖ If necessary, it is intended for water transport to the intervention site and also for transport of potable water. It is suitable for fire extinguishing as well as extinguishing fires in open spaces.
- ❖ Its short wheelbase and its overall length reduces the radius of rotation and makes it easier to operate the vehicle in a narrow surroundings.
- ❖ Tank pumper is equipped with a fire extinguishing pump of normal and high pressure, one high pressure rapid intervention hose reel with high pressure water nozzle and a 5.000 litres water tank located on the chassis between two compartment for firefighting equipment.



FLAMMIFER



Flammifer d.o.o • Ulica akademika Milana Heraka 22 • 47280 Ozalj • Croatia

Tel.: +385 (0)47/731-048 • +385 (0)47/731-068 • +385 (0)47/ 731-088 • Fax: +385 (0)47/731-008 • GSM: +385 (0)91/6645-631

www.flammifer.hr • www.facebook.com/FlammiferOzalj • flammifer@flammifer.hr



Basic firefighting equipment

- ❖ 5000 L water tank made of PPC
- ❖ Normal and high pressure pump type:
 - FPN 10-2000, FPH-40-250
- ❖ High pressure rapid intervention hose reel of 60 or 80 m in length with electrical reeling and high pressure water nozzle
- ❖ Ladders for roof access to superstructure
- ❖ Brackets of firefighting equipment defined by the client

Superstructure

- ❖ Complete superstructure is made of light material (aluminium)
- ❖ Two aluminium roller shutters with bar lock on each side of the vehicle
- ❖ On the back side door or roller shutter with a bar lock
- ❖ Internal superstructure LED Lighting is turned on during opening of the superstructure
- ❖ LED lighting of the surroundings, laterally and back
- ❖ Easy removal of firefighting equipment and its large transparency
- ❖ Heavier equipment fitted low and easily accessible

Chassis

Main characteristics of the chassis:

- ❖ MAN TGM 15.250 4x2 EURO 5
- ❖ Short cab for 3 persons (1+2)
- ❖ Wheelbase: 3275 mm
- ❖ Engine power: 250HP/ 180kW
- ❖ Dimensions of the vehicle: LxWxH: 6950x2500x3200 mm
- ❖ GVW: 16.000 kg

Option

- ❖ Light mast with 4 LED reflectors and pneumatic extraction
- ❖ Roof turret: capacity of 1,600 lit./min, mounted on the roof of the superstructure, foldable with manual control of engine's RPM
- ❖ Second HP rapid intervention hose reel with 60 or 80 m of hose
- ❖ NP rapid intervention hose reel with 25 m of hose
- ❖ Rescue winch



Signalization

- ❖ Signalization of the vehicles according to regulations for firefighting vehicles
- ❖ LED Signal light bar on the roof of the vehicle
- ❖ Two LED flashlights on the front and the back of the vehicle
- ❖ Multi-tonal fire siren with PA system
- ❖ Setup for installation of radio
- ❖ All the main signs on the client's language
- ❖ All other signalization according to national regulations

POSSIBILITY OF INSTALLATION OF THE BRACKET AND ARRANGEMENT OF FIREFIGHTING EQUIPMENT ACCORDING TO CLIENT'S REQUIREMENTS.