

FF TLF 6000

Tank pumper

Made in Croatia



Characteristics

- ❖ The Flammifer FF TLF 6000 is a tank pumper, 15.5 t GVW, with a short cab for up to 3 persons.
- ❖ If necessary, it is intended for water transport to the intervention site and also for transport of potable water. It is suitable for fire extinguishing as well as extinguishing fires in open spaces.
- ❖ Its short wheelbase and its overall length reduces the radius of rotation and makes it easier to operate the vehicle in a narrow surroundings. The four-wheel drive enables easier to move in the rugged terrain.
- ❖ Tank pumper is equipped with a fire extinguishing pump of normal and high pressure, one high pressure rapid intervention hose reel with high pressure water nozzle and a 6000 litres water tank located on the chassis between two compartment for firefighting equipment.



FLAMMIFER





Basic firefighting equipment

- ❖ 6.000 L water tank made of PPC
- ❖ Normal and high pressure pump type:
 - FPN 10-2000, FPH-40-250
- ❖ High pressure rapid intervention hose reel of 60 or 80 m in length with electrical reeling and high pressure water nozzle
- ❖ Ladders for roof access to superstructure
- ❖ Brackets of firefighting equipment defined by client

Superstructure

- ❖ Complete superstructure is made of light material (aluminium)
- ❖ Two aluminium roller shutters with bar lock on each side of the vehicle
- ❖ On the back side door or roller shutter with a bar lock
- ❖ Internal superstructure LED Lighting that is turned on during opening of the superstructure
- ❖ LED lighting of the surroundings, laterally and back
- ❖ Easy removal of firefighting equipment and its large transparency
- ❖ Heavier equipment fitted low and easily accessible

Chassis

Main characteristics of the chassis:

- ❖ MAN TGM 13.250 BL 4x4 EURO 5
- ❖ Short cab for 3 persons (1+2)
- ❖ Wheelbase: 3250 mm
- ❖ Engine power: 250 HP/184 kW
- ❖ Dimensions of the vehicle: LxWxH: 6550x2500x3200 mm
- ❖ GVW: 15.500 kg

Option

- ❖ Light mast with 4 LED reflectors and pneumatic extraction
- ❖ Roof turret: capacity of 1,600 lit./min, foldable with manual control of engine's RPM
- ❖ Second HP rapid intervention hose reel with 60 or 80 m of hose
- ❖ NP rapid intervention hose reel with 25 m of hose
- ❖ Rescue winch



Signalization

- ❖ Signalization of the vehicles according to regulations for firefighting vehicles
- ❖ LED Signal light bar on the roof of the vehicle
- ❖ Two LED flashlights on the front and the back of the vehicle
- ❖ Multi-tonal fire siren with PA system
- ❖ Setup for installation of radio
- ❖ All the main signs on the client's language
- ❖ All other signalization according to national regulations

POSSIBILITY OF INSTALLATION OF THE BRACKET AND ARRANGEMENT OF FIREFIGHTING EQUIPMENT ACCORDING TO CLIENT'S REQUIREMENTS.