

FF TLF 4000/400

Rescue pumper

Made in Croatia



Characteristics

- ❖ The Flammifer FF TLF 4000/400 is a rescue pumper, 16t GVW, with a crew cab for up to 7 firefighters .
- ❖ It is intended for fire extinguishing from smaller towns to larger cities and also for extinguishing fires in open spaces.
- ❖ Its short wheelbase and overall small length makes it easier to operate in a narrow surroundings.
- ❖ The fire engine is equipped with a fire extinguishing pump of normal and high pressure, one high pressure rapid intervention hose reel with high pressure water/foam nozzle and a 4.000 litres water tank and 400 litres foam tank located in the central part of the fire engine`s superstructure.



FLAMMIFER



Flammifer d.o.o • Ulica akademika Milana Heraka 22 • 47280 Ozalj • Croatia

Tel.: +385 (0)47/731-048 • +385 (0)47/731-068 • +385 (0)47/ 731-088 • Fax: +385 (0)47/731-008 • GSM: +385 (0)91/6645-631

www.flammifer.hr • www.facebook.com/FlammiferOzalj • sales@ flammifer.hr



Basic firefighting equipment

- ❖ 4000 L water tank made of PE-HD
- ❖ 400 L foam tank made of PE-HD
- ❖ Normal and high pressure pump type:
 - FPN 10-2000, FPH-40-250
- ❖ High pressure rapid intervention hose reel of 60 or 80 m in length with electrical reeling and high pressure water/foam nozzle
- ❖ Ladders for roof access to superstructure
- ❖ Brackets of firefighting equipment defined by the client

Supstructure

- ❖ Complete superstructure is made of light material (aluminium)
- ❖ Three aluminium roller shutters with bar lock on each side of the vehicle
- ❖ On the back side door or roller shutter with a bar lock
- ❖ Internal superstructure LED Lighting is turned on during opening of the superstructure
- ❖ LED lighting of the surroundings, laterally and back
- ❖ Easy removal of firefighting equipment and its large transparency
- ❖ Heavier equipment fitted low and easily accessible



Chassis

Main characteristics of the chassis:

- ❖ MAN TGM 15.290 4x2 BB
- ❖ Crew cab for 7 persons (1+2+4)
- ❖ Wheelbase: 3875 mm
- ❖ Engine power: 290 HP/ 213 kW
- ❖ Dimensions of the vehicle: LxWxH: 7660x2530x3315 mm
- ❖ GVW: 16.000 kg

Option

- ❖ Light mast with 4 LED reflectors and pneumatic extraction
- ❖ Roof turret: capacity of 1,600 lit./min, mounted on the roof of the superstructure, foldable with manual control of engine's RPM
- ❖ Second HP rapid intervention hose reel with 60 or 80 m of hose
- ❖ NP rapid intervention hose reel with 25 m of hose
- ❖ Rescue winch

Signalization

- ❖ Signalization of the vehicles according to regulations for firefighting vehicles
- ❖ LED Signal light bar on the roof of the vehicle
- ❖ Two LED flashlights on the front and the back of the vehicle
- ❖ Multi-tonal fire siren with PA system
- ❖ Setup for installation of radio
- ❖ All the main signs on the client's language
- ❖ All other signalization according to national regulations

POSSIBILITY OF INSTALLATION OF THE BRACKET AND ARRANGEMENT OF FIREFIGHTING EQUIPMENT ACCORDING TO CLIENT'S REQUIREMENTS.